

Bracket Selection Guide

Control Valve Maker	Valve Range	Nominal size DN [mm]/[inch]	For use with	For use with	For use with
			NRD actuator	NV, NVG, NVF actuators	AV...-R actuators
			Lift up to 5.5mm	Lift up to 20mm	Lift up to 50mm
ARI (EU)	BR 486 / BR 485/ BR 487	15...50	-	UNV-027	-
Cazzaniga (EU)	V2BM / V3BM	15...50	-	UNV-012	-
	V2BM..LN / V3BM..LN	15...50	-CA	-	-
Controlli	VSB/VSB..F	15...50	-	UNV-036 * ¹⁾	-
Trend	GIB../1	15...50	-	UNV-036 * ¹⁾	-
Danfoss	(H)VF2/ (H)VL2/ (H)VRB2	15...50	-	UNV-038 * ²⁾	-
	(H)VE2	25...50	-	UNV-038 * ²⁾	-
	(H)VFS2	15...50	-	UNV-038 * ²⁾	-
	VR2	15...25	-	UNV-038 * ²⁾	-
	(H)VF3 / (H)VL3 / (H)VRB3 / (H)VRG3	15...50	-	UNV-038 * ²⁾	-
Danfoss -Trata	BELIMO H4..H7	1/2"...3"	-	UNV-002	-
Honeywell (EU)	V5011R / V5049A	15...50 (65)	-	UNV-015	-
	V5013R	15...50	-	UNV-015	-
	V5050A / V5328A / V5329A / 5329C	15...80	-	UNV-015	-
	V5095A	20...80	-	UNV-015	-
	V3350(1) / V3360(1) / V3450(1) / V3460(1)	100..150	-	-	UAV ^{*5)}
Honeywell (USA)	V5011 / V5013 Series	1/2"...3"	-	UNV-006	-
	V5011N / V5013N Series	1/2"...3"	-	UNV-006	-
HORA (EU)	BR216RAG / BR316RAG	1/2"...2"	-	UNV-024	-
	BR206GG / BR216GG / BR306GG / BR316GG	15...50 (65)	-	UNV-024	-
	BR225RG	15...25	-	UNV-024	-
Johnson Controls (EU)	VG720. / VG740. / VG780.	15...20	-	UNV-019	-
	VG720. / VG740. / VG780.	25...50	-	UNV-030	-
	BM-2..2 / BM-2..8	15...50	-	UNV-030	-
	VBF-0..4 / VBF-2..4 / VBF-0..8 / VBF-2..8	15...50	-	UNV-034	-
	VG82../ VG84../ VBD-4..4 / VG88../ VG89../ VBD-4..8	15...40	-	UNV-034	-
			-	-	UAV ^{*5)}
Johnson Control (USA)	V-3754 / V-3974 / V-4324 / V-5844	3/4"...2"	-	UNV-008	-
	VG7000 Series	1/2"...3/4"	-	UNV-009	-
Landis (USA)	Powertop/Series VP 658	1/2"...1 1/4"	-	UNV-004	-
	Flowrite/Series VP591	1/2"...1"(2")	-	UNV-005	-
Osby (EU)	MTV / MTR	15...50	-	UNV-025 * ³⁾	-

Notes:

1) Available Quarter 2, 2003

2) Available Quarter 2, 2003

3) Osby valves of size DN 15-25 may only be operated with an actuating force of 750N (75% reduction)

4) The UNV-010 does not belong to any valve manufacturer. It contains the universal bracket and coupling without any stem and valve neck adapter.

5) Available Quarter 2, 2003

Bracket Selection Guide

Control Valve Maker	Valve Range	Nominal size DN [mm]/[inch]	For use with	For use with	For use with
			NRD actuator	NV, NVG, NVF actuators	AV... -R actuators
			Lift up to 5.5mm	Lift up to 20mm	Lift up to 50mm
Robertshaw (USA)	V6600 / V6700	1/2"...2"	-	UNV-007	-
	V6800	3/4"	-	UNV-007	-
Sauter (EU)	V6R..F/ VXD..F/ VXE..F/V6F..F/V6G..F/V6S..F	15...50	-	UNV-018	-
	B6R..F/BXD..F/ BXE..F/B6F..F/B6G..F/B6S..F	15...50	-	UNV-018	-
			-	-	UAV ⁵⁾
Satchwell (EU)	MZ / VZ	1/2"...2"	-	UNV-023	-
	MJF / VSF	15...20	-	UNV-023	-
	VSF/ VZF / VZ / MJF / MZF / MZ	25..150	-	-	UAV ⁵⁾
Siebe/Invensys (USA)	VB7213/VB7223/VB7313	1/2"...2"	-	UNV-001	-
	VB9000	1/2"...1 1/4"	-	UNV-001	-
Siemens (USA)	VF599 Series	1/2"...2"	-	UNV-003	-
Siemens (L&S) EU	V.F21 / V.F31	20/25...80	-	UNV-003	-
	V.G41	1/2"...2"	-	UNV-003	-
	V.F41 / V.F40	15...50 (80)	-	UNV-003	-
	VVF52 / VPF52	15...40	-	UNV-003	-
	V.F61	15/25	-	UNV-003	-
	V.G44 / V.G48	1/2"...1 1/2"	-SI	-	-
	VVI52	15	-SI	-	-
	V.P45	10...20 (40)	-SI	-	-
	V.F31/ V.F40	100..150	-	-	UAV ⁵⁾
	V.F41/ VVF45/ V.F61	65..150	-	-	UAV ⁵⁾
(Universal)	/		-	UNV-010 ^{*4)}	-
Tac (EU)	V241 / V341	15...50	-	UNV-017	-
	V294	15...32	-	UNV-017	-

Notes:

1) Available Quarter 2, 2003

2) Available Quarter 2, 2003

3) Osby valves of size DN 15-25 may only be operated with an actuating force of 750N (75% reduction)

4) The UNV-010 does not belong to any valve manufacturer. It contains the universal bracket and coupling without any stem and valve neck adapter.

5) Available Quarter 2, 2003